



Specification

Model No	AMK501
Ports switch	VGA D-sub 15 pin, USB or PS/2 keyboard Mouse
Drawer Design	1U, Single Slide Rail self-locking device
Weight	10 kgs
Dimension	442.4 x 44 x 410 mm (W x H x D)
Power Supply	Built-in 60W, 90~264VAC, Operating Temp: -20~70°C
Construction	Heavy-duty steel
Keyboard	104-key industrial keyboard with touchpad Option KB: CH, FR, GR, IT, JP, KR, PT, RU, SP, UK, US
Physical Security	2 thumb screws to secure LCD monitor
Protection	Tempered glass protect LCD screen
Power Consumption	3 watts stand-by, 25 watts in-use
Temperature	Operation: 0 ~ 50°C Storage: -20 ~ 60°C
Approvals	CE, FCC class A, RoHS

Features

- Meets EIA310c & IEC-3 specifications
- 1U, Single Rail, built-in 17.3" LCD keyboard drawer
- Built-in 17.3" LCD Monitor, 1920x 1080 resolution
Option: 17.3", 1600x 900 resolution
- USB or PS2 interface keyboard and touchpad
- 104-key industrial keyboard with touch pad
- 1U, 410mm short depth and lightweight
- 2 thumb screws to lock 17.3" LCD monitor
- Built-in rail self-locking device
- Tempered glass protect LCD screen

LCD Display

Size	17.3"
Resolution	1920x 1080 (Option: 1600x 900)

Ordering Information

AMK501-17PBUS

1U, 17.3", 1600x 900 LCD keyboard drawer, PS2 KB/MS with 1.8m KVM cable

AMK501-17UBUS

1U, 17.3", 1600x 900 LCD keyboard drawer, USB KB/MS with 1.8m KVM cable

AMK501-17WPBUS

1U, 17.3", 1920x 1080 LCD keyboard drawer, PS2 KB/MS with 1.8m KVM cable

AMK501-17WUBUS

1U, 17.3", 1920x 1080 LCD keyboard drawer, USB KB/MS with 1.8m KVM cable

Option

- USB or PS2 port
- 80W, 24~ 48VDC Power Supply
- Keyboard layout: CH, FR, GR, IT, JP, KR, PT, RU, SP, UK, US