

IWF 6320H/6320M

Industrial IP67 Outdoor Hopping/Mesh/Mobility Access Point

Dual RF, Dual Band, 802.11 a/b/g/n



Main Features

- Dual Radios and compliant with IEEE 802.11a/b/g/n 2 x 2 MIMO
- Fast roaming (hand-over switch time less than 20 ms)
- Smart installation utilities: Distance calculation, Antenna alignment and site survey tools
- 48VDC PoE input
- Gigabit Ethernet Waterproof RJ45
- WEP, WPA, WPA2-PSK/EAP (IEEE 802.1X/RADIUS, TKIP and AES)
- Operating temperature range from -35 to 75°C

Product Overview

The IWF 6320 series are enterprise and carrier-grade 802.11n Dual Radios Outdoor Wireless Access Point which offers customer a robust and high performing solution for PTP/PTMP/Hotzone/Hopping/Mesh/Mobility Wi-Fi applications in both license-free 2.4GHz and 5GHz bands.

The IWF 6320 series are the most ideal candidate for Service Providers looking to deliver carrier-grade wireless services to multiple market segments such as Railway train, Bus, MRT fast roaming, campuses Mesh network, hospitality, healthcare, warehousing and wider metropolitan area deployments.

Designed to meet customer needs in a broad range of industries, the IWF 6320 offer the following benefits :

Flexible wireless backbone deployment options

Multiple radio interfaces were integrated by NEXCOM core data switching technology inside the IWF 6320 series. Each radio interface can be configured independently to meet different wireless connectivity purposes. With the fast data switching between multiple radio interfaces, the backbone throughput will remain in a high level even after several relays between APs.

High-performance wireless backbone

With the next generation 802.11n MIMO technology, the IWF 6320 offer data link rate up to 300Mbps in each single radio interface. Short Guard Interval and Frames Aggregation methodology configurations improve the efficient of backbone usage.

IWF 6320 Series Category

Model	Radio Spec.
IWF 6320H	Hopping AP, Dual Radios, IEEE 802.11 a/b/g/n Dual-Band 2x2 MIMO, High Power
IWF 6320M	Mesh/Mobility AP, Dual Radios, IEEE 802.11 a/b/g/n Dual-Band 2x2 MIMO, High Power

Specifications

Wireless Radio

- Dual 2 x 2 MIMO radios

Frequency Ranges

- USA : 2.400 ~ 2.483 GHz, 5.15 ~ 5.35 GHz, 5.725 ~ 5.825 GHz
- Europe: 2.400 ~ 2.483 GHz, 5.15 ~ 5.35 GHz, 5.47 ~ 5.725 GHz
- Japan: 2.400 ~ 2.497 GHz, 5.15 ~ 5.35 GHz, 5.47 ~ 5.725 GHz
- China: 2.400 ~ 2.483 GHz, 5.725 ~ 5.85 GHz

RF Output Power: (± 2dBm)

- IEEE802.11a
 - 24dBm@6M (all)

- 21dBm@54M (all)
- IEEE802.11b
 - 24dBm@1M (all)
 - 24dBm@11M (all)
- IEEE802.11g
 - 25dBm@6M (all)
 - 22dBm@54M (all)
- IEEE802.11a/n HT20
 - 24dBm@MCS0/8 (all)
 - 18dBm@MCS7/15 (5180MHz)
 - 17dBm@MCS7/15 (5825MHz)

- IEEE802.11a/n HT40
 - 22dBm@MCS0/8 (all)
 - 17dBm@MCS7/15 (5190MHz)
 - 16dBm@MCS7/15(5795MHz)
- IEEE802.11g/n HT20
 - 25dBm@MCS0/8 (all)
 - 21dBm@MCS7/15 (all)
- IEEE802.11g/n HT40
 - 24dBm@MCS0/8 (all)
 - 20dBm@MCS7/15 (all)

Receive Sensitivity

- IEEE802.11a
 - -82dBm@6M, 1Rx
 - 95/-91dBm@6M, 2Rx
 - -65dBm@54M, 1Rx
 - 79/-75dBm@54M, 2Rx
- IEEE802.11b
 - -82dBm@1M, 1Rx
 - 92/-88dBm@1M, 2Rx
 - -76dBm@11M, 1Rx
 - 92/-88dBm@11M, 2Rx
- IEEE802.11g
 - -82dBm@6M, 1Rx
 - 95/-91dBm@6M, 2Rx
 - -65dBm@54M, 1Rx
 - 80/-76dBm@54M, 2Rx
- IEEE802.11a/n HT20
 - -82dBm@MCS0, 1Rx
 - 95/-91dBm@MCS0, 2Rx
 - -64dBm@MCS7, 1Rx
 - 77/-73dBm@MCS7, 2Rx
- IEEE802.11a/n HT40
 - -79dBm@MCS0, 1Rx
 - 91/-87dBm@MCS0, 2Rx
- -61dBm@MCS7, 1Rx
- -73/-69dBm@MCS7, 2Rx
- IEEE802.11g/n HT20
 - -82dBm@MCS0, 1Rx
 - 95/-91dBm@MCS0, 2Rx
 - -64dBm@MCS7, 1Rx
 - 77/-73dBm@MCS7, 2Rx
- IEEE802.11g/n HT40
 - -79dBm@MCS0, 1Rx
 - 92/-88dBm@MCS0, 2Rx
 - -61dBm@MCS7, 1Rx
 - 74/-70dBm@MCS7, 2Rx

Ethernet

- 10/100/1000 Base-TX MDI/MDI-X RJ-45 x 1
- Compliant with :
 - IEEE802.3/802.3u
 - Hardware based 10/100/1000, full/half, flow control auto negotiation

Bridge Mode

- Layer 2 Switching Learning Technology
- Spanning Tree Protocol -IEEE 802.1d STP/IEEE 802.1w RSTP
- Store-and-Forward
- Static IP
- DHCP server
- IEEE 802.1q Tag VLAN
- IEEE 802.1p VLAN Priority Based QoS

Router Mode

- DHCP Server
- RIP
- IP Filter
- Port Filter
- Port Forward
- DMZ Support
- Static Route

Security

- Hide SSID

- MAC filtering ACL
- WEP 64/128/152 bits
- IEEE 802.1x EAP-TLS/EAP-TTLS/MSCHAPv2/GTC
- WPA/WPA2 PSK/EAP with TKIP/CCMP AES based Encryption

Management

- HTTP(s) Web GUI
- Telnet
- SSH
- CLI commands
- SNNP v2c and V3 standard.(Private MIB)
- Syslog
- Layer management Utility
- Management VLAN Tag
- NTP client
- Firmware upgrade
- Configuration Backup and Restore
- Factory default configuration

Utility

- Ping test
- RSSI and Path loss Calculation
- Wireless Site survey
- Antenna Alignment Tool
- System Status
- Link Information

Advanced Technology

- Multiple Hopping (up to 10 hops with more than 100Mbps throughput)
- Wireless Bandwidth Limitation
- Support MESH/Mobility function in IWF 6320M

Physical and Power

- Support 48Vdc Power over Ethernet
- Form Factor: Pole/Wall mountable
- Dimension: 220 x 220 x 77 mm
- Weight: 2.0kg (3.7kg mount kit included)
- Outdoor IP67 rated

Environment Protection

- Operating temperature: -35°C to 75°C
- Storage temperature: -35°C to 75°C
- Humidity: 0% to 95% maximum (Non-condensing)
- Vibration: Random 0.3g

Certification

- FCC
- CE
- RoHS compliant

Package Contents

- IWF 6320H(M) unit x 1
- 48Vdc power adaptor x 1
- PoE injector x 1
- Pole/Wall mount kit x 1

Ordering Information

- IWF 6320H-US (P/N: 10T00632003X0)
- IWF 6320H-EU (P/N: 10T00632000X0)
- IWF 6320M-US (P/N: 10T00632003X0)
- IWF 6320M-EU (P/N:10T00632002X0)

Wireless Accessories

- Outdoor omni-directional antenna 2.4~2.5GHz 8dBi (P/N: 603ANT0008X00)
- Outdoor directional antenna 5.1-5.9GHz 15dBi (P/N: 603ANT0013X00)
- ARRESTER DC-6 GHz N-MALE TO N-FEMALE (P/N: 7A00000066X00)
- Low Loss Cable, LC-CFD400L1, Length = 1M (P/N: 6023300106X00)