



FRM220-4G-3S

4G Transponder (2R) with Optical Line Protection

2
4G Transponder

The FRM220-4G-3S is a 2R 4G optical regeneration device, which consists of Re-amplification and Re-shaping. The transponder card converts a data signal to the correct wavelength for transmission on a specific channel by supporting SFP optics on both line side and client side interfaces. 1+1 Automatic optical line Protection Switching is supported for the aggregate fiber ports. When the FRM220-4G-3S card is placed in the FRM220 rack with SNMP management, the management can view the converter card's status, type, version, fiber link status and alarms. The card can be configured to enable or disable the port, reset the port and perform diagnostic loop backs.

Features

- Multiple protocol supported at bit rates 28Mbps to 4.25Gbps
- (Fast Ethernet, Gigabit Ethernet, OC -3, OC -6, OC -12, STM-1, STM-4, STM-16, FC -1, FC -2, FC -4)
- Network management via Web, Telnet, SNMP in central FRM220 chassis
- Local configuration via DB9 console port (when placed in CH01M or CH02M)
- Digital diagnostic monitoring of SFP module
- Perform optical repeater function (Re-amplification, Re-shaping)
- Facility loopback on both Client / Line sides
- 1+1 optic fiber protection
- Link Fault Pass-Through (LFPT)
- Auto Laser Shutdown (ALS)
- Detect transceiver transmitter error alarm


Specifications

Optical Interface	Connector	SFP LC
	Data rate	28Mbps to 4.25Gbps
Regeneration	Re-amplification	
	Re-shaping	
Loop back	Line/Client	
Fiber	MM 62.2/125µm, 50/125µm.	
	SM 9/125µm	
Wavelength	MM 850, 1310nm	
	SM 1310, 1550nm	
	WDM 1310T/1550R, 1550T/1310R	
	CWDM 1470 ~ 1610nm	

Indications	LED (PWR, Line Link, Client Link, Test, Loop back, Port Active, Alarm)
Power Input	12VDC
Power Consumption	< 12W
Dimensions	155 x 88 x 23mm (D x W x H)
Weight	120g
Temperature	0 ~ 50°C (Operating), -10 ~ 70°C (Storage)
Humidity	10 ~ 90% non-condensing
Certification	CE, FCC, RoHS compliant
MTBF	65,000 hrs

Application

Managed 4G 2R Transponder with Fiber Protection



Ordering Information

Model Name	Description
FRM220-4G-3S	4G 2R Transponder with fiber protection, (optional SFP module)

Note: This card may be set by DIP switch and placed in CH02M chassis with fan, or set by serial console if placed in CH01M chassis